

OPTICAL FIBER ARRAY AND MANUFACTURE OF DIE


Patent number: JP11174274
Publication date: 1999-07-02
Inventor: SUNAGA KEI; ISHIDA HIDETOSHI; KAKII TOSHIAKI
Applicant: SUMITOMO ELECTRIC IND LTD
Classification:
- International: G02B6/36; B29C33/38; B29C33/42; G02B6/30
- european:
Application number: JP19970342480 19971212
Priority number(s):

Report a data error here

Abstract of JP11174274

PROBLEM TO BE SOLVED: To provide the optical fiber array of excellent temperature characteristics and high density.

SOLUTION: At a ferrule 1, a V groove part 1a is formed at a front part, a coated part mounting part 1b is formed at a rear part, beam-like parts 1c are provided on both sides and a flange part 1d is provided on the rear part. The ferrule 1 is formed by the molding of synthetic resin whose linear expansion coefficient is smaller than the one of glass. In the state of arranging an optical fiber 3a at the V groove part 1a and adding pressurizing force by a pressing lid 2, an adhesive material 4 is poured to the gap of the ferrule 1 and the pressing lid 2 and the optical fiber 3a and a coating 3b at the rear part of the V groove part 1a and they are integrally fixed.



BEST AVAILABLE COPY

Data supplied from the esp@cenet database - Patent Abstracts of Japan